



▲ LSG405

# LIBRARY SECURITY GATE

**Model: LSG405, LSG406**

Andea library security gate adopts 3D sensing patent technology (Patent No.: ZL 2011 1 0442003.7). It can promptly sense RFID labels omni-directionally within 3D sensing zoom, support ISO 15693 RFID labels, initiative and passive alarm modes. Under initiative alarm mode, there are AFI, EAS and AFI+EAS alarm for option. Andea Library security gate can be assembled densely, that is one entrance can up to 10set security gate abreast, its widest identifying width is 90cm. This product is extensively applied at entrance of library and archives.

## Main Features

- ▶ Supported Alarm Modes: AFI, EAS and EAS+AFI
- ▶ Integrated infrared counting function
- ▶ Support passive alarm
- ▶ Integrated 3D omni-directional sensing technology
- ▶ With noise-detected function, can detect interference around
- ▶ One entrance support up to 10pcs gates and consist of 9channels
- ▶ Built-in sound/light alarm prompt module, sound can be adjusted by remote controller



▲ LSG406

## Technical Specification

| Model Name          | LSG405  | LSG406   |
|---------------------|---|--|
| Compatible Protocol | ISO15693  |  |
| Alarm Mode          | EAS,AFI,EAS+AFI   |  |
| Passive Alarm       | Support   |  |
| EMI Detection       | Support   |  |
| Width of Channel    | 90cm  |  |
| Power Supply        | AC 100~240V 50~60Hz   |  |
| Maximum Power       | 30W (20W rated power)   |  |
| Housing Material    | Acrylic and sheet metal   |  |
| Waterproof          | Not waterproof  |  |
| Dimension (L*W*H)   | Whole Unit :1664*636*118mm<br>Antenna :1662*600*60mm<br>Base :636*118mm | Whole Unit :1662*636*118mm<br>Antenna :1728*540*82mm<br>Base:636*118mm |
| Weight              | 23kg/set  | 21kg/set   |
| Working Temperature | -20℃~60℃  |  |
| Storage Temperature | -45℃~85℃  |  |
| Relative Humidity   | 5%~80%  |  |

