



# A2系列A2Series

不带屏专业功率放大器Professional power amplifier without screen



型号Model	立体声Stereo sound 8Ω	H350	H550	H750
额定功率Rated power1KHz, 0.5% THD+N	立体声Stereo sound 4Ω	2 x 350W 2 x 550W 960W	2 x 600W 2 x 850W 1560W	2 x 750W 2 x 1200W 2100W
桥接单声道模式Bridge mono mode 8Ω		20Hz-20kHz, +1/-1dB		
频响范围Frequency response range		≤0.05%		
总谐波失真Total harmonic distortion (THD)		≥150:1	≥160:1	≥200:1
阻尼系数Damping coefficient		97dB	97dB	96dB
信噪比Signal-to-noise ratio		0.775V/1V/1.4V		
输入灵敏度Input sensitivity		> 80dB		
输入共模抑制 Input common mode rejection		≥65dB		
分离度Degree of separation		> 20k (平衡) / > 10k (非平衡)		
输入阻抗Input impedance		68	86	99
电压增益Voltage gain		1000W	1600W	2200W
整体功耗 Overall power consumption		Professional four-pin output socket connection 482x88x298mm		
输出连接Output connection		10.5kg	12.5kg	15kg
尺寸Size (W×H×D)				
净重Net weight				

## 应用范围Scope of application

## 产品特性Product features:

- ▶ 会议室Meeting room
  - ▶ 多功能报告厅  
Multifunctional lecture hall
  - ▶ 体育场Stadium
  - ▶ 酒吧Bar、KTV
  - ▶ 剧院Theater
1. There are 3 modes of stereo, parallel and bridge connection.
  2. With DC protection, overload protection, short circuit protection, overheat protection, input voltage protection, IC protection circuit, sensitive and fast make the machine safer.
  3. The scientific and reasonable heat dissipation system can effectively solve the heat dissipation 8Ωor 4Ωproblems inside the equipment regardless of working at 84, and make the equipment work at normal temperature.
  4. The well-tested electronic components and advanced and reasonable circuit design make the sound quality more perfect.
  5. A series products have low noise and use high-efficiency toroidal transformers.